

INDEPENDENT BATTERY CERTIFICATE



CERTIFICATE NUMBER: 42A7E679-F62B-4E50-B7B0-5FEFB716615F

VEHICLE

BRAND: Honda
MODEL: e - 35,5 kWh

MILEAGE: 27,465 km
VIN: JHMZC7840LX203595
DATE AND TIME:
20/08/2026, 11:12

EXECUTED BY: Jifeline Networks BV


RESULTS

Independent
STATE OF HEALTH (SOH)

83.8 %

ENERGY

24kWh | 29kWh




WLTP RANGE

184km | 220km

RATING

BENCHMARKING

How does your vehicle
compare to comparable
vehicles?



CHECKS

Battery Management System (BMS) ✓
Battery Sensor ✓
Battery Measurements ✓
Battery Cell Voltages ✓
Vehicle Communication ✓



SCAN FOR DETAILS

EVALUATION

FAIR HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in fair condition.

The drive battery is therefore officially AVILOO Certified.

Marcus Berger

Dr. Marcus Berger, CEO



ENERGY

	Gross	Net (Nominal)	Usable
Current:	29.7kWh	23.9kWh	25.5kWh
New:	35.5kWh	28.5kWh	30.5kWh

RANGE

	WLTP	Typical
Current:	184km	
New:	220km	

EXECUTION PROTOCOL

AVILOO Box connected.	11:12:40
FLASH Test started.	✓
Vehicle detected.	✓
Starting data acquisition.	✓
Finished data acquisition.	✓
Analyzing data.	✓
Analysis completed.	✓

SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓


BMS

	Value	Status
BMS State of Charge (SoC)*:	94%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	84%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	29.1°C	31.0°C	1.9°C	✓
Cell Voltage	4.086V	4.096V	11mV	✓
Pack Voltage	392.7V			
Average Current	-0.9A			

CELL VOLTAGES DIAGRAM



*The values shown here were read directly from the vehicle's battery management system (BMS) and are calculated and provided by the vehicle manufacturer. The State of Health (SoH) displayed corresponds to the value reported by the BMS and is CARA-certified.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.