

INDEPENDENT BATTERY CERTIFICATE



CERTIFICATE NUMBER: 078D9544-28B3-48EA-A023-D4D7A5A6CDD9

VEHICLE

BRAND: Audi
MODEL: e-tron 55 - 95 kWh

MILEAGE: 47,299 km
VIN: WAUZZZGE5NB039162
DATE AND TIME:
28/09/2026, 13:20

EXECUTED BY: Jifeline Networks BV

RESULTS

Independent
STATE OF HEALTH (SOH)

96.9 %

ENERGY 83kWh | 86kWh




WLTP RANGE 432km | 446km

RATING

BENCHMARKING

How does your vehicle
compare to comparable
vehicles?



CHECKS

Battery Management System (BMS)	✓
Battery Sensor	✓
Battery Measurements	✓
Battery Cell Voltages	✓
Vehicle Communication	✓



SCAN FOR DETAILS

EVALUATION

EXCELLENT HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in excellent condition.

The drive battery is therefore officially AVILOO Certified.

Marcus Berger

Dr. Marcus Berger, CEO



ENERGY

	Gross	Net (Nominal)	Usable
Current:	92.0kWh	83.3kWh	80.9kWh
New:	95.0kWh	86.0kWh	83.6kWh

RANGE

	WLTP	Typical
Current:	352-432km	303km
New:	364-446km	313km

EXECUTION PROTOCOL

AVILOO Box connected.	13:20:13
FLASH Test started.	✓
Data acquisition started.	✓
Vehicle detected.	✓
Data acquisition completed.	✓
Data analysis started.	✓
Data analysis completed.	✓

SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓

BMS


	Value	Status
BMS State of Charge (SoC)*:	92%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	96%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	16.1°C	16.1°C	0.0°C	✓
Cell Voltage	4.045V	4.048V	3mV	✓
Pack Voltage	437.1V			
Average Current	-0.5A			

CELL VOLTAGES DIAGRAM

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1 - 20	4.045	4.047	4.047	4.047	4.045	4.047	4.047	4.047	4.047	4.045	4.047	4.048	4.047	4.047	4.045	4.045	4.047	4.047	4.047	4.047
21 - 40	4.047	4.048	4.047	4.045	4.047	4.047	4.045	4.047	4.047	4.047	4.048	4.047	4.047	4.047	4.047	4.047	4.047	4.045	4.047	4.047
41 - 60	4.045	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047
61 - 80	4.045	4.047	4.047	4.047	4.047	4.047	4.047	4.048	4.047	4.047	4.047	4.045	4.047	4.045	4.047	4.045	4.045	4.047	4.047	4.047
81 - 100	4.045	4.045	4.045	4.047	4.047	4.047	4.047	4.047	4.047	4.045	4.045	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047
101 - 108	4.047	4.047	4.047	4.045	4.047	4.047	4.047	4.047	4.047	4.045	4.045	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047	4.047



*The values shown here were read directly from the vehicle's battery management system (BMS) and are calculated and provided by the vehicle manufacturer. The State of Health (SoH) displayed corresponds to the value reported by the BMS and is CARA-certified.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.